

Gelovit 200



Hydrocolloid duplicating unit with smart sensor technology.

Gelovit 200 is the next generation duplicating unit featuring a more powerful motor and smart sensor technology for fast, accurate duplication.

The Gelovit 200 offers three fully adjustable temperature settings, a 99 hour programmable timer for delayed starts, and a four zone heating system to maintain exact temperature and prevent overheating.

Features

Precise, Reliable Operation

- Standard working temperature is reached in 4 hours.
- Automatically maintains the cycle from melt to working temperature for consistent duplications.
- Self-cleaning outlet valve will not clog with hardened material.

Software Support

- Stores settings and temperatures for all melting cycles.
- Specify preset or programmable melting cycles for consistent accuracy.
- Large LED display shows temperature, processing time and error codes.
- Signal lamps indicate the process status.

Powerful Drive Unit

- No cutting required. Powerful motor even cuts hardened material in the tank.

Smart Sensors

- Temperature tolerance: $\pm 3^{\circ}\text{F}$.
- Three temperature settings: *Melting*, *Standard Working*, and *Reduced Working*.
- Four zone heat distribution prevents overheating.

Stylish New Design

- Stainless steel reinforced housing reduces vibration and mechanical stress.
- Control panel is ergonomically positioned for optimum viewing and use.
- Large, centrally located outlet valve and integrated drain provides easy discharge.

Specifications

Height23"
Width13"
Depth14"
Capacity	1.5 gal
Duplications.....	± 19 units
Weight	45 lbs
Rated Voltage	110 volt
Warranty	Limited 2 Year



WiroGel® M

Multi-propose hydrocolloid is designed to be used with refractory and gypsum materials, as well as pour acrylics.



Kombi Flask

Unique plastic design ensures even, stress free cooling of hydrocolloid. Unique wedge design prevents rotation.